



Product Sheet

Rasor RS1S

Category: Cutting machines, Hand-held cutting machines

Rasor RS1S – Battery-powered shears for composite materials

The RASOR® RS1S is a professional battery-powered pair of shears for composite materials. It is ergonomic, robust and offers excellent cutting performance. The blades feature tungsten steel inserts with micro-serrated edges, specially developed for composite materials, ensuring clean cuts without the material jamming.

- Designed for composite materials and technical textiles
- Blades with tungsten inserts and micro-serrated edges
- Lightweight at just 370 g including the battery

Product description

Rasor RS1S – Professional scissors for composite materials

The RS1S has been developed for cutting composite materials and technical textiles. The blades are made of steel with tungsten inserts and feature micro-serrated edges that ensure clean cuts and reduce the risk of the material jamming.

The Li-Ion® battery has a capacity of 5 Ah. The motor operates at a speed of 19,000 rpm, enabling the blades to move 80 times per second.

The shears feature smart button technology with a safety lock and automatic cutting mode. The integrated laser guide line enables you to follow a line for straight cuts.

Weighing just 370 grams including the battery, the RS1S is designed for prolonged and effortless use. It can be used on various types of composites, technical textiles, and combination and hybrid materials. The ergonomic design allows you to make both straight cuts and contours whilst maintaining a clear view of the material.

Description

- Designed for composite materials and technical textiles
- Micro-serrated blades with tungsten inserts
- Smart button technology with safety lock and automatic cutting mode
- Integrated laser guide line for straight cuts
- Lightweight at 370 g including battery

Technical Specification

Machine Specifications	
• Leaf description	Steel with tungsten inserts (Widia®), micro-serrated
• Blade speed	80 rpm
• Cutting capacity	18 mm
• Power	32 W
• Battery	2.7–4.2 V Li-ion, 5 Ah, rechargeable with LED indicator
• Charging time	150 mins
• Weight including battery	370 g
• Total weight including packaging	0.5 kg
• Minimum light level for work	200 LUX
• Vibrations during start-up	< 2.5 m/s²
• Temperature range	0–55 °C
• Humidity range	10–95 per cent, non-condensing