

Product Sheet

Heat press Transmatic TS 3P

Category: Textile printing accessories

Transmatic TS 3P – Powerful & efficient pneumatic heat press for professional printing

The Transmatic TS 3P is a high-performance, pneumatically controlled heat press that guarantees even and precise pressure when fixing textile prints. With its swivel heat plate and side opening, you get maximum working space and ergonomic handling, perfect for both small and large productions.

- Pneumatic control – Even and constant pressure for professional results.
- Swivel heat plate – Ergonomic design with convenient side opening.
- Precise temperature and time control – Digital control with visual feedback.

Product description

Transmatic TS 3P – Powerful & efficient pneumatic heat press for professional printing

The Transmatic TS 3P is a high-performance, pneumatically controlled heat press that guarantees even and precise pressure when fixing textile prints. With its swivel heat plate and side opening, you get maximum working space and ergonomic handling, perfect for both small and large productions.

The strong construction and adjustable press pressure make it ideal for all types of textile printing, from DTG printing to transfer and sublimation. Equipped with digital and electronic instruments, you get precise temperature and time control, as well as clear recommendations in the event of any errors.

The interchangeable base plate provides great flexibility and makes it easy to adapt the press to different garments and print sizes. To maximise its capacity, the TS 3P requires a separate compressed air source, ensuring consistent and powerful press pressure for perfect results every time.

Description

- Pneumatic control – Even and constant press pressure for professional results.
- Swivel heating plate – Ergonomic design with convenient side opening.
- Precise temperature and time control – Digital control with visual feedback.
- Replaceable base plates – Customise the pressing surface for different garments and prints.
- Stable & powerful construction – Perfect for DTG, transfer and sublimation printing.

Technical Specification

Machine Specifications

Heating plate	50 × 40 cm
Underlay	50 × 40 cm, 15 × 38 cm, 15 × 15 cm (interchangeable)
Temperature range	50°–255° C
Time	Adjustable 0–999.9 seconds
Pressure	800 g/cm ²
Power supply	230V, single-phase
Energy consumption	2.2 kW (1.0 kW/h)
Net weight	70 kg / 85 kg
Compressed air requirements	Requires separate compressed air source