



Product Sheet

Global FB 3600

Category: Industrial sewing machines

Maximum precision and speed with the Global FB 3600 series

Consists of professional flatbed coverstitch machines with 3 or 4 needles. They are fast, durable and flexible, with features such as differential feed, automatic lubrication and multiple accessories for various sewing tasks.

- High speed and precision – ideal for professional production.
- Differential feed – ensures even and flexible seams in different materials.
- Automatic lubrication

Product description

Maximum precision and speed with the Global FB 3600 series

The Global FB 3600 series is a range of advanced flatbed coverstitch machines for professional sewing. The machines are available in different models with 3 or 4 needles and are equipped with features such as differential feed for even seams, automatic lubrication for longer life and high production speed. Several models offer additional features such as thread trimming, pneumatic presser foot lift and tape edging capability. The machines are often supplied complete with motor, control box and accessories, making them both versatile and efficient for various types of sewing work.

- High speed and precision – ideal for professional production.
- Differential feed – ensures even and flexible seams in different materials.
- Automatic lubrication – minimises maintenance and increases the machine's service life.
- Versatility – machines for 3 or 4 needles, with functions for tape edging and cover seams.
- Complete delivery – many models come with motor, control box and all accessories.

Available in these models

FB 3603-56 AUT

- Flatbed, 3-needle coverstitch machine with upper and lower seams
- Automatic lubrication and differential feed
- Pneumatic presser foot lift and upper and lower thread trimmers
- Supplied complete with Ho Hsing direct drive mini servo motor and control box

FB 3603-64 BFC

- Flatbed, 3-needle coverstitch machine with differential feed
- Multi-functional: suitable for regular sewing, tape binding and cover stitches
- All parts for the variations are included

FB 3653-56 TMD

- Flatbed, 3-needle coverstitch machine with differential feed
- Equipped with upper feed device and right-side bobbin thread cutter

FB 3604-60

- Flatbed, 4-needle coverstitch machine with differential feed
- Needle spacing: 6.0 mm
- Automatic lubrication and high speed

Technical Specification

Machine Specifications	
Integrated motor	Yes
Automatic thread cutter	Yes
Automatic lubrication	Yes
Automatic presser foot lift	Yes
Needle spacing	4.8 – 5.6 – 6.4 mm
Maximum stitch length	4.5 mm
Press foot lift	6 mm
Maximum speed	6,000 rpm