

Product Sheet

SW-7329H

Category: Industrial sewing machines

SW-7329H – Free arm machine for heavy materials

The SW-7329H is a powerful 1-needle shuttle stitch machine with a 440 mm long free arm, developed for leather, rubber, plastic and canvas. Perfect for shoes, bags and other cylindrical products.

With a large looper for longer stitching, a 360° rotating presser foot and a stitch length of up to 7 mm, it delivers precision and stability even in the most demanding materials – a reliable choice for shoemakers and craftsmen.

- Free-arm machine with long arm
- Ideal for extra heavy materials
- 360° rotating presser foot

Product description

SW-7329H – Free-arm machine for extra heavy materials and shoe repairs

The SW-7329H is a powerful 1-needle shuttle stitch machine with a free arm and a long arm of 440 mm, designed for sewing extra thick materials such as leather, rubber, plastic and canvas. It is ideal for repairing and manufacturing shoes, boots, slippers, bags and other cylindrical products, making it the perfect choice for shoemakers and craftsmen.

The large gripper allows for longer sewing without interruption, while the 360° rotating presser foot provides superior flexibility and precision, facilitating the sewing of rounded shapes and hard-to-reach areas. With a maximum stitch length of 7 mm, the machine handles even demanding materials with stability and accuracy.

The SW-7329H is the ultimate machine for professional shoe repair and sewing heavy materials.

Description

- Free-arm machine with long arm – 440 mm arm length for sewing larger products and cylindrical materials.
- Perfect for extra heavy materials – Sews leather, rubber, plastic, canvas and similar heavy textiles.
- Large hook – Enables longer sewing without frequent bobbin changes.
- 360° rotating presser foot – Maximum freedom of movement for sewing curved and hard-to-reach areas.
- Stitch length – Max 7 mm, perfect for strong and durable seams.

Comes complete with

- Shoemaker's table (600×590 mm)
- Shoemaker's stand
- Servo motor with positioning, 550W, 1-phase grounded

Technical Specification

Machine Specifications

• Number of needles	1
• Maximum number of stitches per minute	DP×17 #14
• Lifting height for presser foot	10.5 mm
• Stitch length	Max. 7 mm
• Type of transport	Underfeed and roller feed (for heavy material)