

Product Sheet

Typical GP5

Category: Industrial sewing machines

Typical GP5-III Industrial sewing machine for fur sewing

Typical GP5-III A model, fully configured for sewing medium to thick fur, leather and felt. Equipped with plate feed and double hand wheels for stable control, as well as central lubrication and stitch length up to 4.5 mm.

- Excellent for sewing thick fur with high precision and quality.
- Robust construction with integrated lubrication system and stable feed.
- Many adjustable settings for different production needs.

Product description

Typical GP5-III Industrial sewing machine for fur sewing

Typical GP5-III A model, fully configured for sewing medium to thick fur, leather and felt. Equipped with plate feed and double hand wheels for stable control, as well as central lubrication and stitch length up to 4.5 mm. Description

Description

- Excellent for sewing thick fur with high precision and quality.
- Robust construction with integrated lubrication system and stable feed.
- Many adjustable settings for different production needs.

Supplied complete with

- K-100 table
- Z-stand
- Motor with positioning 240V 1-phase grounded
- Servo motor with positioning 550W

Technical Specification

Machine Specifications

• Maximum speed	up to 1,500 stitches/min (some models 2,000)
• Stitch length	1.5–4.5 mm
• Material thickness	3.0–7.6 mm
• Feeding	plate feeding for even fabric handling
• Lubrication	automatic central lubrication
• Engine	servo motor with high power and low consumption